

AL750

ARTICULATED LOADERS

GEHL®



KEY FEATURES

- ✓ 4-Post Canopy ROPS and FOPS Certified
- ✓ Proportional Auxiliary Hydraulics with Case Drain and Circuit Pressure Dump
- ✓ Inching Pedal
- ✓ Digital Display with Audible and Visual Indicators
- ✓ Differential Lock (Hydraulically Activated Front and Rear)
- ✓ Power-A-Tach® Attachment Mounting System (4-Point, Skid Steer and EuroStyle)
- ✓ Lift Arm with Z-Bar Kinematics, Limited Self-Level and Mechanical Return to Dig
- ✓ Lift Arm Detent
- ✓ Hydraglide™ Ride Control*
- ✓ High-Flow Auxiliary Hydraulics*

*Optional Features

KEY SPECIFICATIONS

- ✓ 7,446 lbs (3378 kg) Static Tipping Load with Bucket Straight
- ✓ 74.4 hp (55.4 kW) gross power @ 2300 rpm
- ✓ 8' 2" (2.48 m) height to top of ROPS
- ✓ 10' 9" (3.28 m) maximum lifting height (below forks)
- ✓ 11' 2" (3.4 m) outer turning radius

IMPERIAL

CAPACITIES	Static tipping load with bucket (straight)	7908 lb
	Static tipping load with bucket (full turn)	5778 lb
	Max. height of bucket pivot point	11 ft 5 in
	Max. lifting height (below forks)	10 ft 9 in
	Breakout force with bucket	5906 daN
Static tipping load with pallet forks - Straight with cab		6354 lb
WEIGHT AND DIMENSIONS	Unladen weight (with forks) with 4-post canopy	10540 lb
	Wheelbase	6 ft 9 in
	Overall width of 4 posts canopy	4 ft 9 in
	Overall cab width	4 ft 9 in
	Overall height with 4 posts canopy	8 ft 2 in
	Overall height with cab	8 ft 2 in
	Tilt-up angle	45 °
	Tilt-down angle	45 °
	Articulation angle	45 °
	Overall width less bucket	5 ft 9 in
Overall length - Less Bucket	14 ft 7 in	
Ground clearance	1 ft	
ENGINE	Engine brand	Deutz
	Engine model	TD3.6 L4
	Engine nom	Stage IIIB
	Number of cylinders / Capacity of cylinders	4 - 220 in ³
	Engine power (Hp / kW)	74.30 Hp / 55 kW
	Max. torque / Engine rotation	243 ft/lbs / 2300 rpm
Engine cooling system	2 radiators water + hydraulic oil	
TRANSMISSION	Transmission type	Hydrostatic
	Number of gears (forward / reverse)	2 / 2
	Max. travel speed (may vary according to applicable regulations)	19 mph
	Travel speed (laden)	19 mph
	Differential lock	Front and rear locking of the machine
Parking brake	Manual	
HYDRAULICS	Hydraulic pump type	Gear pump
	Hydraulic flow - Pressure	18 US gpm / 2901 PSI
	High-Flow Option (l/min)	30 US gpm
	Drive hydraulic system pressure	5511 PSI
TANK CAPACITIES	Hydraulic oil	19 US gal
	Fuel	27 US gal
NOISE AND VIBRATION	Vibration on hands/arms	< 8 ft/s ²
MISCELLANEOUS	Cab certification	ROPS - FOPS cab (level 1)



STANDARD FEATURES

- 12Volt Power Port
- Adjustable and telescopic steering column
- Adjustable arm rests
- Articulation Locking Bar
- Cup Holder
- Differential Lock
- Electronic Hand Throttle
- Front and Rear - Work Lights
- Inching Pedal
- LED work lights - On boom head (Telescopic part)
- Lift Tilt Electronic Lockout Switch
- Master electrical disconnect switch
- Multi-Function Display Screen
- Oscillating Front Frame
- Power-A-Tach® Attachment Mounting System
- Proportional Auxiliary Hydraulics w/ Case Drain & Circuit Pressure Dump
- Removable Rubber Floormat
- Reverse and Brake Tail Lights
- Seven Way Adjustable Air Suspension Seat
- Side View Mirrors
- Tilt & Lift Arm Float Detent with Detent Disable
- Horn
- Two-Speed Hydrostatic Drive System

OPTIONAL FEATURES

- 3-inch Seatbelt
- Back-Up Alarm
- Hydraglide™ Ride Control
- LED Work Lights
- License Plate Holder
- Bluetooth radio
- High-Flow Auxiliary Hydraulics

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT