

ALT750

ARTICULATED LOADERS

GEHL®



KEY FEATURES

- ✓ 4-Post Canopy ROPS and FOPS Certified
- ✓ Proportional Auxiliary Hydraulics with Case Drain and Circuit Pressure Dump
- ✓ Inching Pedal
- ✓ Digital Display with Audible and Visual Indicators
- ✓ Differential Lock (Hydraulically Activated Front and Rear)
- ✓ Power-A-Tach® Attachment Mounting System (4-Point, Skid Steer and EuroStyle)
- ✓ Telescopic Lift Arm with Z-Bar Bucket Linkage and Mechanical Self-Level
- ✓ Lift Arm Float Detent
- ✓ Hydraglide™ Ride Control*
- ✓ High-Flow Auxiliary Hydraulics*

*Optional Features

KEY SPECIFICATIONS

- ✓ 7,714 lbs (3499 kg) Static Tipping Load with Bucket Retracted
- ✓ 74 hp (55 kW) Gross Power @ 2300 rpm
- ✓ 8' 2" (2.48 m) Height to Top of ROPS
- ✓ 16'6" (5.04 m) Hinge Pin Height with Bucket Extended
- ✓ 13' 3" (4.03 m) Outer Turning Radius

IMPERIAL

| | | IMPERIAL |
|------------------------------------|--|---------------------------------------|
| CAPACITIES | Static tipping load with bucket (straight) | 7714 lb |
| | Static tipping load with bucket (full turn) | 4012 lb |
| | Max. payload with forks as per EN 474-3 (80%) | 3527 lb |
| | Max. height of bucket pivot point | 16 ft 6 in |
| | Max. lifting height (below forks) | 15 ft 11 in |
| | Maximum outreach | 10 ft 10 in |
| | Breakout force with bucket | 4990 daN |
| | Static tipping load with bucket (retracted) | 7714 lb |
| | Static tipping load with bucket (extended) | 4012 lb |
| | Bucket hinge pin height (retracted) | 154 in |
| Bucket hinge pin height (extended) | 198 in | |
| WEIGHT AND DIMENSIONS | Unladen weight (with forks) with 4-post canopy | 12300 lb |
| | Overall cab width | 4 ft 2 in |
| | Overall height with 4 posts canopy | 8 ft 2 in |
| | Articulation angle | 40 ° |
| | Overall width less bucket | 6 ft 5 in |
| | Overall length - Less Bucket | 18 ft 10 in |
| | Standard tires | 405/70-20 |
| | Ground clearance | 1 ft |
| | | |
| ENGINE | Engine brand | Deutz |
| | Engine model | TD 3.6 L4 |
| | Engine norm | Stage IIIB |
| | Number of cylinders | 4 |
| | Engine power (Hp / kW) | 74.30 Hp / 55 kW |
| | Max. torque / Engine rotation | 243 ft/lbs / 2300 rpm |
| Engine cooling system | 2 radiators water + hydraulic oil | |
| TRANSMISSION | Transmission type | Hydrostatic |
| | Number of gears (forward / reverse) | 2 / 2 |
| | Max. travel speed (may vary according to applicable regulations) | 19 mph |
| | Travel speed (laden) | 12 mph |
| | Differential lock | Front and rear locking of the machine |
| Parking brake | Manual | |
| HYDRAULICS | Hydraulic pump type | Gear pump |
| | Hydraulic flow - Pressure | 18 US gpm / 2901 PSI |
| | High-Flow Option (l/min) | 29 US gpm |
| | Drive hydraulic system pressure | 5511 PSI |
| TANK CAPACITIES | Hydraulic oil | 19 US gal |
| | Fuel | 30 US gal |
| NOISE AND VIBRATION | Vibration on hands/arms | < 8 ft/s ² |
| MISCELLANEOUS | Cab certification | ROPS - FOPS cab (level 1) |

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



STANDARD FEATURES

- 12Volt Power Port
- Adjustable and telescopic steering column
- Adjustable arm rests
- Adjustable Seat 5-Way
- Articulation Locking Bar
- Cup Holder
- Differential Lock
- Electronic Hand Throttle
- Front and Rear - Work Lights
- Inching Pedal
- Lift Tilt Electronic Lockout Switch
- Master electrical disconnect switch
- Multi-Function Display Screen
- Oscillating Front Frame
- Power-A-Tach® Attachment Mounting System
- Proportional Auxiliary Hydraulics w/ Case Drain & Circuit Pressure Dump
- Removable Rubber Floormat
- Reverse and Brake Tail Lights
- Side View Mirrors

OPTIONAL FEATURES

- 12Volt Power Port
- 3-inch Seatbelt
- Strobe Light
- Adaptive air suspension heated fabric seat - With electric lumbar adjustment - GRAMMER
- Additional Set of Front Auxiliary Hydraulics
- Back-Up Alarm
- Cabin with Heat
- Cabin with Heat and Air Conditioning
- Speed control
- Hydraglide™ Ride Control
- LED Work Lights



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT