

V330 GEN-2

COMPACT LOADERS

GEHL®



KEY FEATURES

- ✓ All-Tach® Attachment System (Universal-Type)
- ✓ Vertical Style Lift Path
- ✓ 4 Cylinder Turbo Diesel Engine
- ✓ Hydraloc™ System
- ✓ ROPS/FOPS Level II
- ✓ Dual T-Bar, Hand/Foot or Joystick Control System
- ✓ Zero Maintenance Axles with 8-Bolt Rims
- ✓ Acoustical Sound Material and Deluxe Headliner

KEY SPECIFICATIONS

- ✓ Operating capacity (50%) - 3,300 lbs. (1497 kg)
- ✓ Overall height to top of ROPS - 82" (2083 mm)
- ✓ Gross Power - 72 hp (53.7 kW) @ 2500 rpm
- ✓ Yanmar / 4TNV98C-NMS / Tier IV
- ✓ 217 ft.-lbs. (294.2 Nm) @ 1625 rpm max torque
- ✓ 131.2" (3332 mm) height to hinge pin
- ✓ 71.6" (1819 mm) machine width - less bucket
- ✓ 9,090 lbs. (4123 kg) operating weight

		IMPERIAL
CAPACITIES	Operating Capacity At 50% Tipping Load	3300 lb
	Operating Weight	9090 lb
	Tipping capacity	6600 lb
WEIGHT AND DIMENSIONS	Wheelbase	49 in
	Overall Operating Height - Fully Raised	172 in
	Height to Hinge Pin - Fully Raised	131 in
	Dump angle at full height	42 °
	Dump height	99 in
	Overall length with bucket	153 in
	Dump reach - Full height	32 in
	Rollback at ground	29 °
	Seat to ground height	41 in
	Overall width less bucket	72 in
	Bucket Width	74 in
	Ground clearance	9 in
	Overall length - Less Bucket	119 in
Clearance Radius - Front with Bucket	94 in	
Rear departure angle	25 °	
PERFORMANCES	Travel speed (unladen)	8 mph
	Travel Speed with Two-Speed Option - Maximum	12 mph
WHEELS	Standard tires	14.00 x 17.5 HD
ENGINE	Engine brand	Yanmar
	Engine model	4TNV98CT-CNMS
	Engine norm	Stage IV, Tier 4 final
	Max. torque / Engine rotation	217 ft/lbs / 1625 rpm
	Power source	Diesel
	Engine power (Hp / kW)	72 Hp / 52.70 kW
	Battery voltage	12 V
	Starter	3 kW
HYDRAULICS	Standard flow - Auxiliary hydraulics	24 US gpm
	High-Flow Auxiliary Hydraulics - Option	35 US gpm
TANK CAPACITIES	Fuel	24 US gal
	Hydraulic tank capacity	11 US gal
	Displacement	0.87 US gal
NOISE AND VIBRATION	Noise to environment (LwA)	101 dB
	Whole-Body Vibration (ISO 2631-1)	4 ft/s ²
	Vibration on hands/arms	< 5 ft/s ²

GEHL Company reminds users to read and understand the operator's manual before operating any equipment. Also, make sure all safety devices and shields are in place and functioning properly. GEHL reserves the right to add improvements or make changes in specifications at any time without notice or obligation.



STANDARD FEATURES

- 12Volt Power Port
- Adjustable 2-inch Seat Belt
- Anti-Vandalism Lock Provisions
- Front and Rear - Work Lights
- Hand/Foot Controls
- Operator Restraint Bar
- Pilot Joystick Controls
- ROPS/FOPS Level II Overhead Guard
- Servo-Controlled Hydrostatic Drive
- Fuel gauge with low level indicator
- Battery charge indicator lamp
- Hour meter
- Hydraloc™ Safety System
- Lift Arm Support Device

OPTIONAL FEATURES

- 3-inch Seatbelt
- Back-Up Alarm
- Battery Disconnect
- Ceiling light
- Engine Block Heater
- Heat & Defrost
- Hydraglide™ Ride Control
- LED Work Lights
- Power-A-Tach® Attachment Mounting System
- Rear view mirror
- Rotating Beacon
- Selectable Self-Leveling Hydraulic Lift Action
- Simplified lifting system without spreader bar
- Sliding Side Windows
- Suspension Seat
- Swing-out Cab Door



One Gehl Way, West Bend, WI 53095
Phone: (262) 334-9461



GEHL COMPACT EQUIPMENT