

Technical sheet :

ME 320 US



Technical characteristics		Imperial	
1.1	Manufacturer		Manitou
1.2	Model Name		ME 320 US
1.3	Power source		Electrical - Lead
1.4	Operator type		Seated
1.5	Max. capacity	Q	4409 lb
1.6	Load center of gravity	c	20 in
1.8	Load distance, centre of drive axle to fork	x	14 in
1.9	Wheelbase	y	58 in
Weight			
2.1	Service weight		7650 lb
2.2	Weight on front axle (laden) / rear axle (laden)		10472 lb / 1587 lb
2.3	Weight on front axle (Unladen) / rear axle (Unladen)		3373 lb / 4277 lb
Wheels			
3.1	Tires type		Solid tires
3.2	Dimensions of front wheels		200/50-10
3.3	Dimensions of rear wheels		15x4,5-8
3.5	Number of front wheels / rear wheels		2 / 1
3.5.2	Number of drive wheels		2
3.6	Front wheel gauge	b10	36 in
3.7	Rear wheel gauge	b11	7 in
Dimensions			
4.8	Seat height/stand height	h7	39 in
4.7	Height of overhead guard (cabin)	h6	80 in
4.12	Height of towing bar (coupling height)	h10	20 in
4.19	Overall length	l1	121 in
4.20	Length to face of forks	l2	79 in
4.21	Overall width	b1	44 in
4.22	Forks section / width / length	s / e / l	2 in x 5 in x 42 in
4.23	Fork carriage ISO 2328 (class/form) A/B		2A
4.24	Fork carriage width	b3	39 in
4.31	Ground clearance below mast	m1	4 in
4.32	Ground clearance at centre of wheelbase	m2	4 in
4.33	Aisle Width for pallets 1000 x 1200 crossways	Ast	132 in
4.34	Aisle width for 800 x 1200 pallet lengthways	Ast	137 in
4.35	Turning radius	Wa	65 in
Performances			
5.1	Travel speed (laden / unladen)		9 mph-9 mph
5.2	Lifting speed (laden / unladen)		1 ft/s-1 ft/s
5.3	Lowering speed (laden / unladen)		2 ft/s-1 ft/s
5.5	Drawbar pull (Laden / Unladen)		900 daN / 930 daN
5.7	Gradeability (laden / unladen)		13 % / 15 %
5.10	Service brake		Oil bath
Engine			
6.1	Number of drive motor / Drive motor rating S2 60 min		2 / 4.50 kW
6.2	Lift motor rating at S3 15%		8.60 kW
6.3	Battery according to DIN 43531/35/36 A, B, C		DIN43531 A
6.4	Battery voltage / capacity		48 V / 690 Ah
6.6	Energy consumption according to VDI cycle (kWh/h)		4.70 kWh/h
Miscellaneous			
8.1	Type of drive control		Electronic
8.2	Working hydraulic pressure for attachments		2611 PSI
8.3	Oil flow rate for attachments		9 US gpm
8.4	Measured/guaranteed mean noise level at the ear of the operator		< 70 dB
8.4	Sound level at the driver's ear according to DIN 12 053		70 dB

ME 320 US - Dimensional drawing





Head Office

B.P. 249 - 430 rue de l'Aubinière
44150 Ancenis Cedex - France

Tel: +33 (0)2 40 09 10 11 - Fax: +33 (0)2 40 09 10 97

www.manitou.com



This publication provides a description of the configuration versions and options for Manitou products, which may differ for equipment. The equipment presented in this brochure may be part of a series, as an option, or it may not be available, depending on the versions. Manitou reserves the right, at any time and without notice, to amend the specifications described and represented. The specifications provided do not bind the manufacturer. For more details, please contact your Manitou agent. This is not a contractually binding document. The presentation of the products is not contractually binding. List of specifications non-exhaustive. The logos as well as the visual identity of the company are owned by Manitou and cannot be used without authorisation. All rights reserved. The photos and diagrams contained in this brochure are only provided for consultation and information purposes.

MANITOU BF SA - Limited company with board of directors - Share capital: 39,668,399 euros - 857 802 508 RCS Nantes